

UNCLASSIFIED

AD NUMBER

AD461759

LIMITATION CHANGES

TO:

Approved for public release; distribution is unlimited.

FROM:

Distribution authorized to U.S. Gov't. agencies and their contractors;
Administrative/Operational Use; 30 MAR 1965.
Other requests shall be referred to Office of Naval Research, Arlington, VA.

AUTHORITY

ONR memo dtd 8 Apr 1968

THIS PAGE IS UNCLASSIFIED

UNCLASSIFIED

AD 4 6 1 7 5 9

DEFENSE DOCUMENTATION CENTER

FOR

SCIENTIFIC AND TECHNICAL INFORMATION

CAMERON STATION ALEXANDRIA, VIRGINIA



UNCLASSIFIED

NOTICE: When government or other drawings, specifications or other data are used for any purpose other than in connection with a definitely related government procurement operation, the U. S. Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

CATALOGED BY: DDC



461759

461759

TYCO LABORATORIES, INC.

BEAR HILL, WALTHAM 54, MASSACHUSETTS
AREA CODE 617
TELEPHONE: 899-1650

ELECTROCHEMISTRY OF FUEL CELL ELECTRODES

by

A. C. Makrides


Principal Investigator

Semi-Annual Technical Summary Report
covering period through March 30, 1965

Contract No. Nonr-3765(00)
dated April 16, 1962
as amended
expiring October 15, 1965

ARPA ORDER No. 302-62
Project Code 9800
Task No. NR 359-443

Prepared For:
OFFICE OF NAVAL RESEARCH
Materials Sciences Division
Washington 25, D. C.



**Best
Available
Copy**

I. INTRODUCTION

The objective of this program is to clarify the molecular basis of electrocatalysis and thereby to provide the necessary scientific framework for the optimization of fuel cell electrodes. Using electrodes of varied chemical composition, we have attempted to show whether their catalytic properties depend primarily upon the intrinsic chemical activity of the individual surface atoms, or upon the energy states of the crystal as a whole. If this distinction can be made, and if quantitative correlations with the atomic or continuum properties can be established, then the design of fuel cell electrodes becomes enormously simplified.

Hydrogen oxidation and reduction, the reduction of oxygen, and the oxidation of formic acid, a soluble organic substance, were selected for these studies because of their relevance to fuel cell systems and because of their relative simplicity. The electrodes used range from amalgams to III-V semiconducting compounds. The approach is to resolve the overall reaction on any given electrode into the elementary steps of adsorption, electron transfer, chemical combination of free radicals, etc., and to determine how the parameters governing the rates of these various steps are related to the electrode composition and structure. The experimental studies currently under way are described below.

II. ELECTROCATALYSIS BY AMALGAM ELECTRODES

The question of whether the continuum properties or the atomic nature of an electrode determines its electrocatalytic properties can be approached directly by using amalgam electrodes. The high overpotential for the hydrogen evolution reaction on mercury makes it easy to detect the effect of catalytic additives. A clean, reproducible surface can be achieved with liquid amalgams by using a dropping electrode; thus, this technique was adopted in our studies. A detailed analysis of the factors affecting hydrogen overvoltage requires measurements of double-layer capacity, activity coefficients, temperature dependence of hydrogen overvoltage, work function, and interfacial tension.

During this report period, the studies of hydrogen overvoltage and double layer capacity on indium and thallium amalgams have been completed. Studies of the interface structure indium amalgams and electrolytes, and the relation of electronic properties of the electrode to the parameters of the hydrogen evolution reaction, have been continued with studies of interfacial tension and work function. The results of some of this work have been presented in Technical Memoranda Nos. 16, 17, and 18, and are summarized below. We have also summarized the work in progress, which will be reported in future technical memoranda.

Double Layer Capacity of Thallium Amalgams

Measurements of double layer capacity and zero charge potential have been made on 10, 30, and 40% thallium amalgams. These results have been compared with existing literature data. The integrated capacity curves agree with literature values for experimental electrocapillary curves. The surface concentration of thallium, at potentials where overvoltage measurements have been made, is one half to three-fourths of the bulk concentration. In contrast to results reported in the literature, the double-layer capacity of 40% thallium amalgam shows no dependence on frequency, within experimental error in the range from 0.5 kc to 10 kc. This work was reported in detail in Technical Memorandum No. 16.

Hydrogen Overvoltage on Thallium Amalgams

Measurements have been made of hydrogen overvoltage, in 0.1 M HClO_4 , at temperatures from 14° to 69°C, at dropping amalgam electrodes containing 10.0 and 40.6 mole percent thallium. The overvoltage is 20 to 30 millivolts higher on 40% thallium amalgam than on mercury. When corrections are made for the effect of the diffuse double layer, the exchange current for hydrogen discharge at 25°C is found to decrease by a factor of 2 on going from mercury to 40% thallium amalgam. The temperature dependence of overvoltage gives an enthalpy of activation (extrapolated to the reversible hydrogen potential) of 22.3 ± 0.4 , 21.2 ± 1.1 , and 23.1 ± 0.3 kcal/mole for mercury, 10% thallium amalgam, and 40% thallium amalgam respectively. Thus, both the overvoltage and the enthalpy of activation are higher on thallium amalgams than on mercury. This work was reported in detail in Technical Memorandum No. 17.

Hydrogen Overvoltage on Indium Amalgams

Hydrogen overvoltage has been measured at temperatures from 14°C to 66°C, using dropping amalgam electrodes containing 10.0, 20.0, 40.0, and 63.0 mole % indium. The enthalpy of activation was extrapolated to the reversible potential, and corrected for the effect of the diffuse double layer. For the most concentrated amalgams, it is approximately 1 kcal/mole lower than for mercury. This change is consistent with the decrease in overvoltage with increasing indium content at constant temperature. This work was reported in detail in Technical Memorandum No. 18.

Interfacial Tension of Indium Amalgams

A method has been developed for determining interfacial tension by fitting a theoretical curve to the experimentally measured shape of a sessile drop. A computer program is used to generate solutions to the non-linear differential equation describing the drop shape. Absolute measurements of interfacial tension for amalgams containing up to 64 mole % indium were made in 0.1 M HClO_4 at 25°C. These were combined with previously

measured values of zero-charge potentials and differential capacity, to generate a family of electrocapillary curves from which the surface excess was calculated using the Gibbs equation. The surface excess is negative, and passes through a maximum negative value at approximately 20 mole % indium. The parameters of the hydrogen evolution reaction on indium amalgams correlate with the bulk electronic properties of the amalgams, but not with the surface composition. This work is summarized in Technical Memorandum No. 19, which will be issued in April, 1965.

Adsorption of Ions on Indium Amalgams

Measurements have been made of the zero-charge potential and double-layer capacity on indium amalgams in fluoride solutions. These results have been compared with our previous measurements in perchloric acid (Technical Memorandum No. 15). The specific adsorption of these ions depends strongly on the concentration of indium in the amalgam. In contrast to mercury, the fluoride ion is more strongly adsorbed than is the perchlorate ion; this difference is greatest at the highest indium concentrations. These data are presently being analyzed in detail. When measurements of interfacial tension in fluoride solutions have been completed, this work will be summarized in a technical memorandum.

Electronic Work Function of Indium Amalgams

One of the most important electronic properties of an electrode in its influence on electrocatalysis is the electronic work function. For thirty years, electrochemists have used a correlation between zero-charge potential and work function which is based on data which may be in error by more than 0.1 volts. The indium-mercury system offers the possibility of examining this relation with an accuracy of ± 0.005 volts over a potential range of nearly 0.5 volts, which is half the accessible range of work functions. From this relation, information can be obtained about the orientation of water molecules at the electrode-electrolyte interface, a factor which is very important in determining the rate of electrocatalytic reactions.

Preliminary experiments using the ionization method for determining the contact potential difference between mercury and the amalgams indicated that superficial oxide films must be completely eliminated in order to obtain accurate measurements. Because of additional uncertainties due to short-term changes in the work function of the reference electrode used in the contact-potential measurement, and the necessity in any case for constructing a high-vacuum system to prevent oxide formation, we have decided to measure the work function photoelectrically. The main advantage of this technique is that it is an absolute measurement.

The vacuum system for preparing the amalgams and for measuring the photocurrent has been built and tested. Both systems can be evacuated to 10^{-8} torr in about three hours with no bakeout. A 1000 w mercury-Zenon lamp, together with a quartz monochromator, will provide the illumination. The light intensity will be monitored by a photo-multiplier, calibrated with a thermopile, and the photocurrent will be measured using an electrometer with a sensitivity of 10^{-13} amp. By preparing the amalgams under a high vacuum, and by gettering the residual oxygen in the system before measurements, it should be possible to maintain an oxygen-free surface for sufficient time to measure the photo-current over a range of wavelengths. From this data, an absolute value of the work function can be calculated for each of a series of indium amalgams.

III. TECHNICAL MEMORANDA AND PUBLICATIONS

Of the memoranda listed in the previous semi-annual report, the following have appeared in print:

1. "Surface Oxidation of Gold", by S. B. Brummer and A. C. Makrides, *J. Electrochem. Soc.* 111, 1122-1128 (1964) (Tech. Mem. No. 6)
2. "Hydrogen Evolution at a Dropping Indium Amalgam Electrode", by J. N. Butler and A. C. Makrides, *Trans. Faraday Soc.*, 60, 1664-1676 (1964) (Tech. Mem. No. 10)
3. "Hydrogen Evolution at a Solid Indium Electrode", by J. N. Butler and M. Dienst, *J. Electrochem. Soc.*, 112, 226-232 (1965) (Tech. Mem. No. 11)
4. "The Use of Large Anodic Galvanostatic Transients to Evaluate the Maximum Adsorption on Pt from HCOOH Solutions", by S. B. Brummer, *J. Phys. Chem.* 69, 562-571 (1965) (Tech. Mem. No. 13)

Thus, all Technical Memoranda through No. 13 have appeared in print with the exception of No. 12, which described a computer program for double layer calculations.

The following have been accepted for publication, and are in press:

Technical Memorandum No. 14: (a) "Galvanostatic Studies of Carbon Monoxide Adsorption on Platinum Electrodes", by S. B. Brummer and J. I. Ford, *J. Phys. Chem.*; (b) "Comparison of Adsorbed Formic Acid and Carbon Monoxide on Platinum Electrodes", by S. B. Brummer, *J. Phys. Chem.*

Technical Memorandum No. 15: "The Electrical Double-Layer on Indium Amalgam Electrodes", by J. N. Butler, M. L. Meehan, and A. C. Makrides, *J. Electroanal. Chem.*

The following Technical Memoranda were issued during this report period.

Technical Memorandum No. 16: "The Electrical Double Layer on Thallium Amalgam Electrodes", by J. N. Butler, accepted by *J. Electroanal. Chem.*

Technical Memorandum No. 17: "Hydrogen Overvoltage at a Dropping Thallium Amalgam Electrode", by J. N. Butler, E. A. Barron-Apps, and M. L. Meehan, submitted to Trans. Faraday Soc.

Technical Memorandum No. 18: "Temperature Dependence of Hydrogen Overvoltage on Indium Amalgams," by J. N. Butler and M. L. Meehan, submitted to Trans. Faraday Soc.

TECHNICAL REPORT DISTRIBUTION LIST

Contract No. Nonr 3765 (OO)

Commanding Officer Office of Naval Research Branch Office 230 N. Michigan Avenue Chicago 1, Illinois (1)	Harry Diamond Laboratories Washington 25, D. C. Attn: Library (1)
Commanding Officer Office of Naval Research Branch Office 207 West 24th Street New York 11, New York (1)	Office, Chief of Research & Development Department of the Army Washington 25, D. C. Attn: Physical Sciences Division (1)
Commanding Officer Office of Naval Research Branch Office 1030 East Green Street Pasadena 1, California (1)	Chief, Bureau of Ships Department of the Navy Washington 25, D. C. Attn: Code 342A (2)
Commanding Officer Office of Naval Research Branch Office Box 39, Navy #100, F. P. O. New York, New York (7)	Technical Library, DLI-3 Bureau of Naval Weapons Department of the Navy Washington 25, D. C. (4)
Director, Naval Research Laboratory Washington 25, D. C. Attn: Technical Information Officer (6) Chemistry Division (2)	Defense Documentation Center Cameron Station Alexandria, Virginia (20)
Chief of Naval Research Department of the Navy Washington 25, D. C. Attn: Code 425 (2)	Commanding Officer U. S. Army Electronics Research and Development Laboratory Attn: SELRA/DR Fort Monmouth, New Jersey 07703 (1)
DDR&E Technical Library Room 3C-128, The Pentagon Washington 25, D. C. (1)	Naval Radiological Defense Laboratory San Francisco 24, California Attn: Technical Library (1)
Department of the Army Supply & Maintenance Command Maintenance Readiness Division Washington 25, D. C. Attn: Technical Director (1)	Naval Ordnance Test Station China Lake, California Attn: Head, Chemistry Div. (1)
U. S. Army Natick Laboratories Clothing & Organic Materials Division Natick, Massachusetts Attn: Associate Director (1)	Commanding Officer Army Research Office Box CM, Duke Station Durham, North Carolina Attn: CRD-AA-IP (1)

Atomic Energy Commission Division of Research Chemistry Programs Washington 25, D. C.	(1)	Dr. Howard L. Recht Astropower, Inc. 2968 Randolph Avenue Costa Mesa, California	(1)
Atomic Energy Commission Division of Technical Information Extension Post Office Box 62 Oak Ridge, Tennessee	(1)	Mr. L. R. Griffith California Research Corporation 570 Standard Avenue Richmond, California	(1)
Commanding Officer U. S. Army Chemical Research and Development Laboratories Attn: Librarian Edgewood Arsenal, Maryland	(1)	Dr. Ralph G. Gentile Monsanto Research Corporation Boston Laboratories Everett 49, Massachusetts	(1)
Commanding Officer ONR Branch Office 495 Summer Street Boston 10, Massachusetts	(1)	Mr. Ray M. Hurd Texas Research Associates 1701 Guadalupe Street Austin 1, Texas	(1)
Director, ARPA Attn: Dr. J. H. Huth Material Sciences Room 3D155 The Pentagon Washington 25, D. C.	(4)	Dr. C. E. Heath Esso Research & Engineering Company Box 51 Linden, New Jersey	(1)
Dr. S. Schuldiner Naval Research Laboratory Code 6160 Washington 25, D. C.	(1)	Mr. R. J. Flannery American Oil Company Whiting Laboratories Post Office Box 431 Whiting, Indiana	(1)
Dr. A. B. Scott Department of Chemistry Oregon State University Corvallis, Oregon	(1)	Dr. Douglas W. McKee General Electric Company Research Laboratories Schenectady, New York	(1)
Inspector of Naval Material 495 Summer Street Boston 10, Massachusetts	(1)	Dr. E. A. Oster General Electric Company, DECO Lynn, Massachusetts	(1)
Mr. R. A. Osteryoung Atomics International Canoga Park, California	(1)	Dr. R. R. Heikes Westinghouse Research Laboratories Beulah Road Pittsburgh, Pa. 15235	(1)
Dr. David M. Mason Stanford University Stanford, California	(1)	Professor Herman P. Meissner Massachusetts Institute of Technology Cambridge 39, Massachusetts	(1)

Mr. Donald P. Snowden General Atomic Post Office Box 608 San Diego 12, California	(1)	Dr. B. R. Sundheim Department of Chemistry New York University New York 3, New York	(1)
Mr. C. Tobias Chemistry Department University of California Berkeley, California	(1)	Dr. E. M. Cohn NASA Code RPP 1512 H Street, N. W. Washington 25, D. C.	(1)
Mr. Y. L. Sandler Westinghouse Research Laboratories Pittsburgh, Pennsylvania	(1)	Dr. E. Yeager Department of Chemistry Western Reserve University Cleveland 6, Ohio	(1)
Dr. Paul Delahay Department of Chemistry Louisiana State University Baton Rouge, Louisiana	(1)	Dr. V. I. Matkovich The Carborundum Company Niagara Falls, New York	(1)
Dr. W. J. Hamer Electrochemistry Section National Bureau of Standards Washington 25, D.C.	(1)	Dr. A. M. Zwickel Department of Chemistry Clark University Worcester, Massachusetts	(1)
Dr. Herbert Hunger Power Sources Division U. S. Army Signal Research & Development Laboratory Fort Monmouth, New Jersey	(1)	Dr. Michael O'Keefe Department of Chemistry Arizona State University Tempe, Arizona	(1)
Dr. T. P. Dirkse Department of Chemistry Calvin College Grand Rapids, Michigan	(1)	Lockheed Aircraft Corporation Missiles and Space Division Technical Information Center 3251 Hanover Street Palo Alto, California	(1)
Dr. George J. Janz Department of Chemistry Rensselaer Polytechnic Institute Troy, New York	(1)	Dr. G. C. Szego Institute for Defense Analysis 1666 Connecticut Avenue, N. W. Washington 9, D. C.	(1)
Mr. N. F. Blackburn E. R. D. L. Materials Branch Fort Belvoir, Virginia	(1)	Dr. R. F. Baddour Department of Chemistry Massachusetts Institute of Technology Cambridge 39, Massachusetts	(1)
Mr. W. M. Lee, Director Contract Research Department Pennsalt Chemicals Corporation 900 First Avenue King of Prussia, Pennsylvania	(2)		

Mr. T. W. Cushing, Manager
Military Service Department
Engelhard Industries, Inc.
113 Astor Street
Newark, New Jersey (1)

Thompson Ramo Wooldridge Inc.
23555 Euclid Avenue
Cleveland 17, Ohio
Attn: J. Ed Taylor (1)
Associate Director, RD&E

Aerospace Corporation
Post Office Box 95085
Los Angeles 45, California
Attn: Library Technical
Documents Group (1)

Dr. Galen R. Frysinger
Electric Power Branch
E. R. D. L.
Fort Belvoir, Virginia (1)

Mr. Robert Post
Lewis Laboratories
NASA
21000 Brook Park Road
Cleveland 35, Ohio (1)

Mr. Nathan Kaplan, Chief
Power Supply Branch 940
Harry Diamond Laboratories
Washington 25, D. C. (1)

Mr. R. Comyn
Power Supply Branch 940
Harry Diamond Laboratories
Washington 25, D. C. (1)

American Cyanamid Company
Stamford Research Laboratories
1937 West Main Street
Stamford, Connecticut
Attn: Mrs. S. P. Moore (1)